




■ SPECIFICATIONS

CONTACT FORM	SPDT
CONTACT RATING	10A 250VAC
OPERATING TEMP.	0 ~ 60°C
CABLE MATERIAL	VCT
FLOAT ENCLOSURE	IP68
SPECIFIC GRAVITY	≥0.7
FLOAT MATERIAL	PP
TEST PRESSURE	0.4MPa
CABLE LENGTH	<input type="checkbox"/> 5M <input type="checkbox"/> _____M
ACCESSORY	To be specified



■ WIRING CONNECTIONS



BLACK / COMMON
RED / N.C.
WHITE / N.O.

RED :
CONTACT CLOSED
WHITE :
CONTACT OPEN
BLACK : COMMON

RED :
CONTACT OPEN
WHITE :
CONTACT CLOSED
BLACK : COMMON



■ INSTRUCTIONS

⚠ CAUTION Do not install products before consulting instruction.

FIG. 1

Plenty of space is required in order to allow the float moving up and down.




FIG. 2

Prevent the float from being affected by waves or running water.




FIG. 3

When combine several floats, the distance between floats should be carefully observed to avoid entanglement.




FIG. 4

When reset the float position, cable should be kept straight to avoid any ring being made.




FIG. 5

The terminal housing should not be mounted in a tank and must be kept dry at any time.

